

### Features

- Frequency Range: 1800MHz to 2200MHz
- Low Cost and RoHS Compliant
- Industry Standard SMT package
- Available in Tape-and -Reel
- 50Ω Characteristic Impedance

### Product Description




The SPC-2201-25H is a 0° two way power splitter designed for applications that require small, low cost, and highly reliable surface mount components. Applications may be found in broadband, wireless, and other communications systems. These units are built Lead-Free and RoHS Compliant. S-Parameters are available on request.



### Specifications

Parameter	Specification			Unit
	Min.	Typ.	Max.	
Frequency Range	1800		2200	MHz
Insertion Loss		0.5	0.8	dB
Isolation	16	23		dB
Return Loss	11	17		dB
Amplitude Balance		0.2	0.5	dB
Phase Balance		4	5	°


Note: Typical values represent midband performance at T=25 °C.




# SPC-2201-25H



**Amplitude Balance**



**Phase Balance**




**Pin Out**

Pin	Name
3	Input
10	Output 1
6	Output 2
1, 2, 4, 5, 7, 8, 9	Ground

**Absolute Maximum Ratings**

Parameter	Rating	Unit
RF Power	+33	dBm
Operating Temperature	-55 to +100	°C
Storage Temperature	-55 to +100	°C

**Package Drawing - S10**



Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability. Specified typical performance or functional operation of the device under Absolute Maximum Rating conditions is not implied.

RoHS status based on EU Directive 2002/95/EC (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by MiniRF, Inc. ("MiniRF") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of MiniRF. MiniRF reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.