



MRFLF0530

50 Ohm Low-Pass Filter

Features

- High Reliability
- Small Surface Mountable Size
- Low insertion loss 1.2 dB
- LTCC built

Applications

- Harmonic Rejection
- VHF / UHF Transmitters / Receivers
- LTE/5G Infra
- Test & Measure

RoHS Compliant and Pb-Free Product



Specifications

Parameter	Specification			Units
	Min	Typ.	Max.	
Passband Frequency	0		530	MHz
Insertion Loss 0 – 530 MHz			1.2	dB
3dB Cutoff Frequency:		700		MHz
VSWR 0 – 530 MHz		1.5		dB
Rejection 820 MHz 945 – 3000 MHz 6200 MHz	20 40 20			dB
Nominal Impedance	50 Ω			

Absolute Max Ratings

Operating Temp	-55°C to 125°C
Storage Temp	-55°C to 125°C

Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended applications of Absolute Maximum Rating conditions to the device may reduce device reliability. Specified typical performance or functional operation of the device under Absolute Maximum Rating conditions not applied.

RoHS Status based on EU Directive 2002/95/EC (at the time of this document revision)

The information in this publication is believed to be accurate and reliable. However, no responsibilities is assumed by MiniRF Inc. for its use, nor for any infringements of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of MiniRF Inc.

Welding Recommendations


Preheat	150°C, 1 minute
Tip Temperature	350°C max
Output Power	80w max
Soldering iron tip size	ϕ 3mm max
Welding Time	3 seconds max

During preheating, the temperature difference between the product surface temperature and the solder temperature must not exceed 150°C. After soldering, during cooling, the temperature difference between the product surface temperature and the solvent temperature must not exceed 100°C. Insufficient preheating may cause surface cracks in the product, leading to a decline in product quality.



MiniRF Incorporated
46560 Fremont BLVD, STE 114
Fremont CA 94538

Tel: 408-228-3533
www.minirf.com



MiniRF


MRFLF0530

50 Ohm Low-Pass Filter



RoHS Compliant and Pb-Free Product

Data



MiniRF

MiniRF Incorporated

46560 Fremont BLVD, STE 114
Fremont CA 94538



Tel: 408-228-3533
www.minirf.com

Connections

Pin 1 / Pin 2	Input
Pin 3 / Pin 4	Ground

Pad Dimensions

Dimensions in mm
Tolerance: $\pm 0.1\text{mm}$



A	B	C	D	E	F	G	H	J	K	L	M	P
3.2	1.6	0.95	0.41	0.8	0.23	4.3	2.2	0.6	3.1	0.6	2.2	1.8

Reflow Soldering Temp Profile

